

IDE Devices Configuration

Primary 0	[40008MB]
Primary 1	[None]
Secondary 0	[CD-ROM]
Secondary 1	[None]
SMART Devices Monitoring	[Enabled]
Large Disk Access Mode:	[DOS]
Local Bus IDE adapter:	[Both]

Diskette Options

Floppy disk controller:	[Disabled]
Legacy Diskette 1	[Disabled]

Video Configuration

Primary Video	[PCI]
PCI VGA Adapter Priority	[Last]
Graphics Aperture:	[128 Mb]
Internal Graphics Devices:	[One]
Memory Size:	[UMA = 32MB]
Boot Display(s)	[Auto]
Local Flat Panel:	[Disabled]

USB Configuration

USB Controllers	[Three Controllers]
EHCI (USB 2.0) Support:	[Enabled]
Legacy USB Support	[Full]
HDD Mode Sense Page 5	[Enabled]
HDD Boot Translation	[Auto]

LAN Configuration

Embedded Ethernet 1	[Enabled]
PXE OPROM:	[Disabled]

Embedded Ethernet 1 Options

Connector Label	LAN 1
Option ROM Scan	[Enabled]
Enable Bus Master	[Enabled]
Latency Timer	[Default]
MAC Address	00.....

PCI Expansion Slot Configuration

PCI Device, Slot #2
PCI Device, Slot #3
PCI Device, Slot #4

Shared PCI IRQs [Share Four]

Peripheral Configuration

Serial port A: [Auto]

Serial port B: [Auto]

Parallel port: [Auto]

Mode: [ECP]

Power Control Configuration

Power Savings: [Customized]

Standby Timeout: [Off]

Resume On Time: [Off]

Resume Time: [00:00:00]

Power Buttorn [On/Off]

After Power Failure: [Stay Off]

PME Wake from S5: [Disabled]

System Monitors Configuration

Chassis Intrusion [Disabled]

Reset chassis intrusion [No]

Secured Chassis [Disabled]

Processor Fan Rate [Two]

System Fan 1 Rate [One]

System Fan 2 Rate [One]

Automatic Fan Control [Use Setup Options]

Advanced Configuration

DDR ECC Operation [Enabled]

Enable memory gap: [Disabled]

Reset Configuration Data: [No]

EMI Reduction [Enabled]

AC97 Audio [Enabled]

APIC – IO APIC Mode: [Enabled]

Console Redirection

COM Port Address	[Disabled]
Baude Rate	[19.2K]
Console Type	[PC ANSI]
Flow Control	[CTS/RTS]
Console connection:	[Direct]
Continue C.R. after POST:	[Off]

Boot Order

Flopp check:	[Disabled]
Summary Screen:	[Disabled]
Boot-time Diagnostic Screen:	[Enabled]
Logo Video Mode	[640x480]
QuickBoot Mode:	[Enabled]
Installed OS	[WinXP or later]
Enable ACPI	[Yes]
POST Errors	[Enabled]