

GENERAL INFORMATION

Lighting control system harnessing and extending the power of WYSIWYG™ visualization and the acclaimed ETC Expression style operation, software and functionality in a fully integrated, networked system.

- APPLICATIONS** University, College, School Theatre
Regional Theatre
TV Studio
Touring Shows
Special Events, Trade Show, Church
- FEATURES** 500, 1000, 2500 or 5000 channels
32,767 dimmers
Expression-style ease of operation
9,999 cues, 255 focus points, 500 groups, 2000 macros
16-bit fades
Hard drive and CD-RW for file storage and transfer
WYSIWYG-style paperwork, drafting and visualization
Comprehensive libraries (over 6000 items)
Wireframe and shaded visualization of stage and blind views
Preview and Storyboard in wireframe and shaded view
Emphasis backup server configuration for synchronized backup
Photo-realistic Rendering
Custom Report and Plot content and layout
Import / Export of WYSIWYG files
Patch and data changes propagate throughout system
Graphic fixture selection
Optional functionality: Emphasis 2D and Emphasis 3D
Supports WYSILink message logging
Full WYSILink option available
- ACCESSORIES** Flat screen monitors
Remote Focus Unit (RFU)
Radio Remote Focus Unit (RRFU)
Wireless Remote Focus Unit (WRFU)
ETCNet2 Video Node
ETCNet2 DMX Nodes
Alpha Numeric Keyboard (included)
Scroll Mouse (included)
Tower Stand
5-port Ethernet hub/switch (included)
19" equipment rack tray
Remote Virtual Face panel
Emphasis Offline Editor

ORDERING INFORMATION

Emphasis Servers

Model #	Description
EMPH-3D-500	3D Server 500 channels
EMPH-3D-1000	3D Server 1000 channels
EMPH-3D-2500	3D Server 2500 channels
EMPH-3D-5000	3D Server 5000 channels
EMPH-3D-500-L	3D Server 500 channels with WYSILink
EMPH-3D-1000-L	3D Server 1000 channels with WYSILink
EMPH-3D-2500-L	3D Server 2500 channels with WYSILink
EMPH-3D-5000-L	3D Server 5000 channels with WYSILink
EMPH-2D-500	2D Server 500 channels
EMPH-2D-1000	2D Server 1000 channels
EMPH-2D-2500	2D Server 2500 channels
EMPH-2D-5000	2D Server 5000 channels
EMPH-2D-500-L	2D Server 500 channels with WYSILink
EMPH-2D-1000-L	2D Server 1000 channels with WYSILink
EMPH-2D-2500-L	2D Server 2500 channels with WYSILink
EMPH-2D-5000-L	2D Server 5000 channels with WYSILink

Emphasis Facepanels

Model #	Description
EMPH-EXPN	Expression ECS Facepanel
EMPH-EXPN-S	Expression ECS Facepanel with SMPTE
EMPH-INST	Insight ECS Facepanel
EMPH-INST-S	Insight ECS Facepanel with SMPTE
EMPH-EXPS	Express ECS Facepanel
EMPH-EXPS24	Express 24/48 ECS Facepanel
EMPH-EXPS48	Express 48/96 ECS Facepanel
EMPH-EXPS72	Express 72/144 ECS Facepanel

Emphasis Accessories

Model #	Description
D-NODE	See DMX Node datasheets for details
V-NODE	ETCNet2 Video Node
M219	LCD Flat Screen Display
M732	Emphasis Server Tower Stand
M733	Emphasis Server 19" rack-mount tray
N1029	5-port Ethernet Switch
4200A1108	Emphasis Dual Video Upgrade Kit (ETC Hardware)
WYSILink	WYSILink
RFU	Remote Focus Unit
RRFU	Radio Remote Focus Unit
WRFU-FL	Wireless Remote Focus Unit, Full System
LPC250	Express Lighting Playback Controller
LPC400, LPC800, LPC1200	Expression Lighting Playback Controller
LPC512	Insight Lighting Playback Controller



SPECIFICATIONS

SYSTEM CAPACITY	32,767 DMX512 dimmers/attributes 500/1000/2500/5000 control channels 9,999 cues 500 groups 255 focus points Effects with up to 100 steps each 2,000 macros 24 submasters/10 pages (108/10 on Insight) Two timed/manual fader pairs Hard drive CD/RW drive Diskette drive Single/Dual VGA outputs
EMPHASIS CONSOLE: FACEPANEL INTERFACE	Playback Monitor Fader status Cue List MIDI/SMPTE Event List Command Monitor Stage Blind Spreadsheet and List Cue, Sub, Group and Focus Point Fader A/B fader and/or C/D fader Spreadsheet Tracksheet Patch Proportional levels 32 User-definable profiles Full integration with data and visualization Park Channel or dimmer Setup Expand Flexichannel (displays only used channels)
PLAYBACK CONTROLS	Faders Two timed/manual fader pairs with Go, Hold, Rate, Clear, and Back keys. Individual last action fade capability for each channel Submasters 24 submasters with bump buttons and integral LEDs (108 on Insight) Encoders Five Moving Light attribute encoders ¹ Rate wheel ¹ Level wheel ¹ Trackpad ² Master slider Blackout button Channel faders and bump buttons (Two-Scene Express only)
INTERFACES	DMX512 Configurable Outputs (four ¹ /two ²) Ethernet MIDI MIDI Show Control MIDI Time Code SMPTE ¹ Remote Focus Unit (RFU) Remote Macro/Go Remote Trigger ² File Server
CONTROL KEYPAD FEATURES	Cue attributes Cues from .1 to 999.9 Split up/down fade times Wait times Follow time Link to cue, macro or submaster Modified rate Label ¹

Eight-part multipart cues Selective cue recording
Channel Functions Lists constructed with And, Thru, Except Sneak sets channel to discrete or fader level in default/specified time Only and Except features for group and channel manipulation Channel Attribute display Independent channel capability Flip provides inversion of pan/tilt or lamp/scroll programming Last Action Channels Dual fader wheels and five control attributes for moving lights ¹ Frame Tables
Moving Light Functions Six pages of attribute encoders ¹ Focus Points 16-bit fade resolution Pop-up displays Dynamic Effects
Group Functions 500 groups with labels Any cue or submaster may be accessed as a group
Submaster Functions Ten pages of 24 submasters with labels, timing and rate attributes (108 on Insight) Bump buttons may be enabled, disabled or solo Range editing of submaster attributes in submaster list Submasters 13-24 (73-108 on Insight) may be individually changed between pile-on and inhibitive. Any Submaster can become a Supermaster of other Submasters
Effect Functions Live effects editing Step-based intensity effects Template-based Dynamic Effects Comprehensive timing effects Customize dynamic templates Effects may be recorded as cues and/or loaded to submasters
Subroutines Subroutines on submasters Up to 26 cue stacks (up to 110 on Insight) 100 steps with level and timing attributes. Multiple step types Multiple playback styles Filter for selective playback Macro firing
Macros Macro list 2,000 macros, 1000 steps each Macros may activate any key or command sequence on the console. Live Learn mode Blind editing Remote Macros (via facepanel and video nodes) Startup Macro
Astronomical Time Clock Program up to 500 events Play back according to date, day of week, time of day Program longitude/latitude of show location Play back in reference to time before/after sunrise or sunset

¹ Expression and Insight facepanels only

² Express facepanels only

SPECIFICATIONS

EMPHASIS SERVER	<ul style="list-style-type: none"> Pentium based processor Hard drive CD/RW drive Floppy drive Sound card USB ports Serial Ports VGA/DVI³ monitor output Parallel printer port 19" rack mountable / desktop Network Printing Network file sharing Partial Show Read Show Mode User log-in
USER INTERFACE	<ul style="list-style-type: none"> Password protected System Manager log-in Extended Windows™ desktop³ Scroll Mouse (any pointing device) Keyboard Hotkeys, drop-down menus, toolbar icons, shortcuts Pop-up windows
DISPLAYS/ USER MODES	<ul style="list-style-type: none"> Emphasis mode <ul style="list-style-type: none"> Console Screen — facepanel screens with wireframe and shaded view³ Console — facepanel screens and virtual console Subroutine Quad — wireframe and shaded³ views Wireframe — plan, section and isometric³ Shaded³ Monitor — one facepanel screen CAD mode <ul style="list-style-type: none"> Wireframe, Quad, Flight case, Shaded³ Data mode <ul style="list-style-type: none"> Spreadsheet, H Select, V Select, Patch, Errors Presentation mode <ul style="list-style-type: none"> Reports, Plots, Images, Worksheet Link mode <ul style="list-style-type: none"> Message log
CONTROL FEATURES	<ul style="list-style-type: none"> Graphic selection of fixtures <ul style="list-style-type: none"> Mouse click Multiple selection <ul style="list-style-type: none"> Mouse click + Ctrl Left click dragged box Right click dragged box, specify by type By layer By Concept Menu tools for <ul style="list-style-type: none"> Fixture home state Intensity Full/Out/Specify Focus Iris Wide/Tight/Specify Colour Palette & Library Console toolbars <ul style="list-style-type: none"> Screen/mode selection, record tools, configurable buttons Virtual console Virtual console <ul style="list-style-type: none"> Clickable softkeys and menu items Faders mirror levels from facepanel Blind editing with visualization for <ul style="list-style-type: none"> Cues Groups Submasters Focus Points Preview Mode — visualize any cue, and current cue +1, +2, +3 Storyboard — visualize multiple cues and activate live from window Rendering³ <ul style="list-style-type: none"> File image, and bitmap output Variable resolution Full color mixing, amber shift, haze, smoke, radosity, shadow, ambient light

CAD FEATURES

CAD FEATURES	<ul style="list-style-type: none"> Comprehensive libraries for <ul style="list-style-type: none"> Fixtures — over 1400 from 72 manufacturers Truss — over 1400 items from 19 manufacturers Theatrical scenic elements, including over 170 people Colour — gel catalogs from 18 manufacturers Gobos — catalogs from 22 manufacturers Accessories, Lens, Lamps, Symbols CAD conventions <ul style="list-style-type: none"> Missing Coordinate XYZ command line Relative & Absolute values Ortho, Snap, Cursor, Origin Undo, Redo, Repeat last command, Group, Ungroup, Move, Rotate, Focus, Mirror Import from .dwg, .dxf Interactive & specified object drawing Dimension & Distance tools Layers & Scenes Extrude, Break, Convert, Divide, Fillet, Array Drawing tools <ul style="list-style-type: none"> Riser, Sphere, Column, Pipe, Line, Circle, Arc, Text Label, Surface, Extruded Surface, Focus Position, Camera, Venue: Black Box, Proscenium Arch, Arena Specified and interactive object creation Fixture property tools <ul style="list-style-type: none"> Point of View³, Shutter³, Barn Door³, Barrel Rotate³, Patch, Accessories Fixture photometrics Quick Tools <ul style="list-style-type: none"> Spot, Unit, Purpose, Focus, Channel, Patch, Dimmer, Circuit, Colour, Gobo Shortcut tools <ul style="list-style-type: none"> Col/Gobo, Fixture, Truss, Accessories, Library, Navigation, Views, Concepts, Palettes Object property tools <ul style="list-style-type: none"> Translucency, Light Emitting Surface, Textures, Materials, Legs & Borders Focus Position with Link to Focus Point Position Manager Patch <ul style="list-style-type: none"> Fixture layer indication Fixture control status EDMX Graphic selection Drag-and-drop patching Spreadsheet data entry & edit Error checking & reporting Data filter Configurable spreadsheets Fully interactive with all data entry in system Dynamically updated from any screen, including changes made at facepanel Configurable reports from data Configurable plot printing Images from render & screen bitmaps Worksheet for plot notes Multi-format output WYSIlink message log Pop-up messages About Dimmer⁴ and About Rack⁴ Node / Device manager⁴ CEM backup look recording & playback⁴ Graphic dimmer error indication in wireframe views⁴ Highlighted dimmer error indication in data views⁴ EDMX monitoring⁴ CEM+: Sensor+ connect browser interface
---------------------	---

DATA FEATURES

PRESENTATION FEATURES

DIMMER MONITORING FEATURES


³ Emphasis 3D system only

⁴ WYSIlink add-on option features. Messaging dependant on AF/Standard option for Sensor Dimming system

Emphasis® Control System

Emphasis Series

TYPICAL SYSTEM RISER



Wire types

-----	local peripherals	standard monitor / mouse / keyboard / printer
————	ETCNet2	category 5 Ethernet (RJ45) – Belden 1583A(UTP)
=====	DMX	DMX (XLR5) – Belden 9729
.....	RFU	RFU (XLR6) – Belden 9728
=====	ETCLink	ETCLink (XLR6) – Belden 9279
-----	ULP	Unison Link Power – Belden 8471 2x#16AWG



Corporate Headquarters ■ 3031 Pleasant View Rd, PO Box 620979, Middleton WI 53562 0979 USA ■ Tel +1 608 831 4116 ■ Fax +1 608 836 1736
London, UK ■ Unit 26-28, Victoria Industrial Estate, Victoria Road, London W3 6UU, UK ■ Tel +44 (0)20 8896 1000 ■ Fax +44 (0)20 8896 2000
Rome, IT ■ Via Ennio Quirino Visconti, 11, 00193 Rome, Italy ■ Tel +39 (06) 32 111 683 ■ Fax +39 (06) 32 656 990
Holzkirchen, DE ■ Ohmstrasse 3, 83607 Holzkirchen, Germany ■ Tel +49 (80 24) 47 00-0 ■ Fax +49 (80 24) 47 00-3 00
Hong Kong ■ Room 605-606, Tower III Enterprise Square, 9 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong ■ Tel +852 2799 1220 ■ Fax +852 2799 9325
Web ■ www.etcconnect.com ■ Copyright © 2006 ETC. All Rights Reserved. All product information and specifications subject to change. 4200L1004 Rev. E Printed in USA 07/06