



SD Individual Dimmer

When things are tight, you need a dimming system that provides an exact fit. The SD-Individual Dimmer from ETC is tailor-made for you.

Each SD is a completely self-contained dimming system. Recessed components and the strong, lightweight case make the SD easy to move and hard to damage. Flexible output and connector options will fit your style.

For distance work, plug in a CH1-6 Single Channel Controller for individual control of up to six connected SDs.

SD-Individual Dimmers from ETC – the fit that gets you out of tight situations.

Features:

- 20, 50 or 100 amp output rating
- Stage pin, Edison or combination input/output connectors
- Fully magnetic circuit breaker
- Built-in control slider
- Steel and extruded aluminum housing
- 3-pin XLR remote control connector
- Local/Remote selector switch

CH1-6 Single Scene Control Console

- Six 3-pin XLR cable connections to SD Remote Control jack
- Six individual channel faders
- Master fader provides proportional control
- LED power indicator





General

Constructed of 16-gauge steel and extruded aluminum
 Fine-texture, scratch-resistant, black finish
 Controls and connectors are recessed for protection
 Dual brass carrying handles
 Local/Remote control toggle switch
 Local control fader
 Three-pin male XLR analog 0-10Vdc remote control connector
 20A units are convection-cooled
 50A and 100A units are forced air-cooled

Dimensions

20amp: 14.5"/37cm H, 4.5"/11cm W, 9"/23cm D
 Weight 14 lbs/6 kgs
50amp: 14.5"/37cm H, 4.5"/11cm W, 9"/23cm D
 Weight 19 lbs/9 kgs
100amp: 14.5"/37cm H, 6.5"/16cm W, 9"/23cm D
 Weight 22.5 lbs/10 kgs

Electrical

Dims resistive loads from 10 watts to dimmer capacity
 50/60Hz 120V or 240V AC
 Edison, stage pin or mixed power connectors for 20amp
 Stage pin power connectors on 50 and 100amp
 95% dimmer efficiency
 Response to control is .5 microseconds or less
 Output curve is IES modified square law
 Fully-magnetic circuit breaker

CH1-6 Single Scene Control Console

General


Constructed of 16-gauge aluminum
 Fine-texture, scratch-resistant, black finish with white silk-screened graphics
 Six individual channel faders with proportional Master fader

Dimensions

2.3"/6cm H, 8.2"/21cm W, 6"/15cm D
 Weight 2.06 lbs/1 kg

Electrical

Connects to SD-Individual dimmer with 3-pin XLR connector cable
 SD-Individual Dimmer provides 12Vdc operating voltage through connector cable
 LED power indicator
 Six 0-10V DC output ports connect up to six individual dimmers



Ordering information

Catalog#	Description
SD2400AA.....	20amp (2.4kW) dimmer with Edison power connectors
SD2400BB.....	20amp (2.4kW) dimmer with stage pin power connectors
SD2400AB.....	20amp (2.4kW) dimmer with stage pin/Edison power connectors
SD6000BB.....	50amp (2.4kW) dimmer with stage pin power connectors
SD12000BB.....	100amp (2.4kW) dimmer with stage pin power connectors

(Please specify either 120 or 240V power when you order)



Electronic Theatre Controls

North America • 3030 Laura Lane Middleton, WI 53562 • Tel: (+1) 608 831 4116 • Fax: (+1) 608 836 1736

Europe • Tel: (+44) 181 896 1000 • Fax: (+44) 181 896 2000 Asia • Tel: (+852) 2799 1220 • Fax: (+852) 2799 9325

Web: www.etconnect.com • Email: mail@etconnect.com COPYRIGHT 1997. SPECIFICATIONS SUBJECT TO CHANGE. REVISED 10/97. 1015L1002